

## **AFTERCARE INSTRUCTIONS**

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting, even the non-scratch cleaners. **NOTE: Never use abrasive detergents or disinfectants or those containing alcohol, hydrochloric acid or phosphoric acid.**

## **GUARANTEE**

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture.

**All products must have access for servicing or replacement during the life of the product.**

In the interests of continuous product development we reserve the right to alter specification as necessary

**TELEPHONE HELPLINE: 0844 701 6273**

Bristan Group Limited  
Birch Coppice Business Park  
Dordon  
Tamworth  
Staffordshire  
B78 1SG  
UK  
A Masco Company  
Website: [www.bristan.com](http://www.bristan.com)  
Telephone: 0844 701 6274  
Facsimile: 0844 701 6275  
Email: [enquire@bristan.com](mailto:enquire@bristan.com)

# BRISTAN

## **Freestanding Bath Shroud Covers (Standpipes)** (LEG C/G/BN)

## **Fitting Instructions & Contents List**



Before starting any installation project please consider:

Prior to drilling into walls, check there are no hidden electrical wires, cables or water supply pipes with the aid of an electronic detector. If you use power tools do not forget:

- Wear eye protection
- Unplug equipment after use

**Please keep these instructions for future reference and request of replacement part**

Standpipes are designed to support taps and mixers near a freestanding bath and concealed pipe work, which feeds up from the floor, to them.

## **INSTALLATION**

**NOTE: - Installation instructions are only a guide, and the order in which the installation is carried out may be altered to suit on-site conditions.**

1. Identify all components and check for completeness, particularly before commencing installation.
2. Loosen the grub screw (1) on the standpipes, remove the flanges (2) and screw them, large diameter uppermost, onto the tails of the taps or mixer (3).
3. The connector (4) supplied can be brazed onto 22mm pipe work (not supplied) to create the vertical feed through the shroud to the taps or mixer. Use a suitable length to allow sufficient movement to aid assembly and to ease further connections below the floor.
4. Place the floor plates (5) in the desired position, mark out screw holes, drill and using wall plugs if necessary, screw plates to the floor.



Before starting any installation project please consider:

Prior to drilling into walls, check there are no hidden electrical wires, cables or water supply pipes with the aid of an electronic detector. If you use power tools do not forget:

- Wear eye protection
- Unplug equipment after use

**NOTE: - Horizontal feed pipe under floor must have a degree of freedom to move up and down.**

5. Slide standpipes (6) over the vertical pipes ensuring sufficient movement to allow connector (4) to reach tails. Use washer (7) to seal between 3 and 4. Connect vertical pipe work to under floor pipe work and test by turning on fitting and letting it run for a few minutes to check all joints and connections for leaks.
6. Screw the standpipes into the floor plates (5). Then secure the taps or mixer in position by locating the shrouds (2) into the top of the standpipes and tightening the grub screws (1).
7. See back page for aftercare instructions.

### **PLEASE NOTE:**

In the unlikely event you find a part missing, please contact our Customer Service helpline on **0844 701 6273** for immediate dispatch of part

