

# **Bath Shower Mixer Fitting Instructions**

Thank you for purchasing this Croydex product. Please follow the fitting and care instructions to ensure that your bath shower mixer set is fitted safely and that it retains its high quality finish.

#### **Bath Shower Mixer Set Contents**

Semi permanent diverter system

Multi-position shower head with easy clean rose

1.5m Flexitube shower hose Fully adjustable riser bar

### **Tools Required**

Drill; Pencil; 5.5mm masonry drill bit; 5.5mm ceramic drill bit (optional); Spirit level; Small flat head screwdriver; Flat head screwdriver; Tape measure.

### KEEP DIY TOOLS OUT OF THE REACH OF CHILDREN

### **Safety Advice**

- 1. Hot water is dangerous always check the water temperature before using the shower. Never leave a child unattended in the bathroom.
- 2. Always take care when using an electric drill, particularly in the bathroom. Always check for hidden cables and pipework before drilling. Always use a residual current circuit breaker (RCCB) when using mains powered tools and take extreme care if there is any water in the working area. Always wear suitable eye protection when drilling.
- 3. If the product is to be fitted on a ceramic tiled wall, a ceramic drill bit should be used. Do not drill mounting holes in the grouted area between tiles. Mask the area around the hole with tape before drilling to prevent damage to the tile.
- 4. Do not connect directly to water heaters or combination boilers. Do not use with water temperatures above 65°C or with water pressures above 50p.s.i.
- 5. Always turn on the cold tap first then add hot water until the desired shower temperature is reached. Avoid running cold water from other outlets as this may affect the temperature of the shower spray.
- 6. Do not use the product as a grab bar.

The Croydex Bath Shower Mixer Set has been designed with safety in mind and incorporates a unique safety shut off valve, which automatically diverts water from the shower head to the bath as soon as the water pressure falls below a predetermined level.

To use the shower, firstly turn on the taps, adjust the water temperature and pull the lever forward to divert water to the shower head.

The pressure of water will hold the lever forward in the shower mode until the taps are turned off. The lever will then automatically revert back to the bath mode position.

### **Diverter Fitting Instructions**

(Note: for the best results the spray head should be fitted 1m (3') or more below the bottom of the cold water tank.)




1. Unscrew the white covers to reveal the rubber tap seals and clips.




2. Push the rubber tap seals over the tap spouts. (A little soap around the spouts might make this easier).



3. Ensure that the screw is pointing upwards and is on the inside face as shown. Tighten the clips with a screwdriver for maximum grip.



4. Connect the shower hose and handset. (Include all washers supplied).



5. Turn on the taps and check for any leaks around the rubber seals. Tighten the clips further if necessary.



6. Replace the white tap covers and tighten the screws.

# **Riser Bar Fitting Instructions**




1. Remove the riser bar bracket caps.



2. Mark the positions for the screw holes ensuring they are vertical.



3. Drill holes using a 5.5mm masonry drill bit. (See note re: ceramic tiles in Safety Advice.)



4. Insert the wall plugs below the plaster or tile level. (If fitting to a tiled surface, the wall plugs should be inserted below the surface of the tile.)



5. Screw the bracket to the wall.



6. Replace the bracket caps.

### **Care Advice**

- To retain the best quality finish, clean the product regularly with a soft damp cloth.
- Do not use abrasive or chemical cleaners, as these will damage the product.

## Please retain this leaflet for future reference.

Croydex Limited, Central Way, Andover, Hants, SP10 5AW, UK Tel: +44 (0) 1264 365881. Fax: +44 (0) 1264 356437 Website: www.croydex.co.uk. E-mail: info@croydex.co.uk.