

Thank you for choosing Bristan, the UK's leading showers and taps expert.

These instructions are for your guidance to a safe and successful installation and should be left with the user. All products manufactured and supplied by Bristan are safe providing they are installed correctly and receive regular maintenance in accordance with these instructions.

- Please read these instructions thoroughly and retain for future use.
- All products manufactured and supplied by Bristan are safe provided they are installed, used correctly and receive regular maintenance in accordance with these instructions.
-  **If you are in any doubt about your ability to install this product safely you must employ the services of an experienced qualified plumber.**
- These fittings need to be installed in accordance with, and meet the requirements of the Water Supply (Water Fittings) Regulations 1999 and Scottish Byelaws 2004.
- **Warning:** Do not operate the mixer if you suspect it is frozen. Do not site the mixer valve where it might be subjected to freezing conditions.
- Remove all packaging and check the contents for damage before starting installation.
- Before starting any installation please consider the following: before drilling into walls, check that there are no hidden electrical wires, cables or water supply pipes. This can be checked with the aid of an electronic detector.
- If power tools are used do not forget to:
  - Wear eye protection
  - Unplug equipment after use
-  **Warning:** It is essential that you thoroughly flush through the pipework in order to remove any remaining swarf, solder, etc before using this product. Failure to carry out this procedure could cause problems or damage.
- This product **must** not be modified in any way as this will invalidate the guarantee.

Bristan's shower accessories are covered by a **5 year guarantee**. This also includes **5 year labour cover\*** (subject to registration) which means that, in the unlikely event that there is a problem in the first year after purchase, we'll send one of our expert engineers to fix it.

\*Labour is provided by an approved Bristan Care engineer or appointed representative. The guarantee only applies to products with a manufacturing fault. There will be a call out charge for any incidents where no fault has been found with the product, or if the issue is due to poor installation or maintenance.

For full terms and conditions please visit [www.bristan.com](http://www.bristan.com).

Part Number: FI WORD/WOSQ

Issue: D1

Bristan Group Ltd. Birch Coppice Business Park  
Dordon, Tamworth, Staffordshire, B78 1SG  
Web: [www.bristan.com](http://www.bristan.com) Email: [enquire@bristan.com](mailto:enquire@bristan.com)

Customer Service: **0844 7016273**

**⚠ Important:** The pipework must be secure and rigid to ensure it does not move.

## 1. Identify position of wall outlet

Identify the position in which the wall outlet is to be installed. Make a suitable hole in the wall surface for the threaded tail.

**⚠ Warning:** Please check for any hidden pipes and cables before drilling into walls.

## 2. Fit wall outlet

Place the wall outlet through the hole and secure in place by tightening the backnut fully. A suitable spanner can be used to tighten the backnut.


## 3. Connect pipework

Connect the supply pipework to the wall outlet using a suitable fitting (an elbow fitting is shown). Connect the supply pipework to the fitting using a compression nut and olive.

## 4. Connect hose

Screw the shower hose (not supplied) onto the outlet ensuring the sealing washer is fitted.

Place wall outlet through hole in the wall



Tighten backnut

