



Vanity basin	Dimension	Weight	Order number
undercounter basin, with overflow, fixings for insta wooden consoles included, without tap platform, 3			
Colors			
00 White Alpin			
Variant			
⊗	370 x 370 mm	6.200 kg	0373370000
Infobox			
Measurements of undercounter models represent	interior measurements		
Sanitary ceramics with the special WonderGliss su time to come. When ordering WonderGliss please add a "1" as el		attractive-looking for a long	
Accessory for ceramics			
Fixing for stone countertops, (with the exception o	f # 046651)	0.200 kg	005028
Recommended faucets			
Single lever basin mixer M Ceramic cartridge, Promm, Flexible connection hoses 3/8 ",, aerator adju Normal spray, chrome, maximum temperature can on installation, recommended operating pressure with pop-up waste set,	istable, n be adjusted		B11020001
Single lever basin mixer M Ceramic cartridge, Promm, Flexible connection hoses 3/8 ",, aerator adju Normal spray, chrome, maximum temperature calon installation, recommended operating pressure with pop-up waste set,	ıstable, n be adjusted		B21020001
Single lever basin mixer M Ceramic cartridge, Promm, Flexible connection hoses 3/8 ",, aerator adjunction adjunction, care and the care and installation, recommended operating pressure without pop-up waste set,	istable, n be adjusted		B11020002



Vanity basin # 0373370000

|< 370 mm >|

Single lever basin mixer M Ceramic cartridge, Projection 139 mm, Flexible connection hoses 3/8 ",, aerator adjustable, Normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	B21020002
Single lever basin mixer M Ceramic cartridge, projection 122 mm, aerator with Easy-clean spray-plate, flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, recommended operating pressure 3 - 5 bar, with pop-up waste set,	WA1020001
Single lever basin mixer M Ceramic cartridge, projection 122 mm, aerator with Easy-clean spray-plate, flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, recommended operating pressure 3 - 5 bar, without pop-up waste set,	WA1020002
3-hole basin mixer 90° ceramic valve, projection 129 mm, aerator with Easy-clean spray-plate, flow rate 5,0 l/min (3 bar), Normal spray, recommended operating pressure 3 - 5 bar, with pop-up waste set,	WA1060005
Single lever basin mixer for concealed installation Normal spray, Ceramic cartridge, aerator with Easy-clean spray-plate, flow rate 5,0 l/min (3 bar), Connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 3 - 5 bar, projection 202 mm,	WA1070004
Single lever basin mixer M FreshStart connection size DN15,	WA1021001
Single lever basin mixer M FreshStart connection size DN15,	WA1021002
Single lever basin mixer M MinusFlow connection size DN15,	WA1022001
Single lever basin mixer M MinusFlow connection size DN15,	WA1022002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.