



Furniture washbasin	Dimension	Weight	Order number
without overflow, without tap platform, ceramic cove continuous flow waste waste included, fixings include mm			
Colors			
00 White Alpin			
Variant			
×	Ø 500 mm	10.500 kg	2365500070
Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come.  When ordering WonderGliss please add a "1" as eleventh digit to the model number.			
Accessory			
Design Siphon		1.500 kg	005036
Suitable products  Vanity unit floor-standing 2 wooden shelves access fr			
sides, including floor mounting, for White Tulip # 236550, 410 x 410 x 410 mm 410 mm			WT4239
Recommended faucets			
Single lever basin mixer XL Ceramic cartridge, Projection 166 mm, Flexible connection hoses 3/8 ",, aerator adjustable, Normal spray, recommended operating pressure 3 - 5 bar, with pop-up waste set,			C11040001
Single lever basin mixer for concealed installation Normal spray, Ceramic cartridge, aerator adjustable, Connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 3 - 5 bar, Projection 174 mm,			C11070003
Single lever basin mixer XL Ceramic cartridge, Projection 166 mm, Flexible connection hoses 3/8 ",, aerator adjustable, Normal spray, recommended operating pressure 3 - 5 bar, without pop-up waste set,			C11040002



## Furniture washbasin # 2365500070

|< Ø 500 mm >|

Single lever basin mixer for concealed installation Normal spray, Ceramic cartridge, aerator adjustable, Connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 3 - 5 bar, Projection 225 mm,	C11070004
Single lever basin mixer XL Ceramic cartridge, Projection 160 mm, Flexible connection hoses 3/8 ",, aerator adjustable, Normal spray, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set, chrome,	WT1040002
Single lever basin mixer for concealed installation Ceramic cartridge, Normal spray, aerator adjustable, Connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 3 - 5 bar, Projection 225 mm, chrome,	WT1070004

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.