


Technical Data Sheet

LEAP – LE70ALU, LE80ALU & LE120ALU



Box Contents:

Leap Mirror | 2x Wall hanging brackets | 4x wall plugs | 4x screws | Instructions booklet

Materials

Frame Material: Extruded Aluminium

Glass: 5mm PVC Backed

FAQ's:	Units	LE70ALU	LE80ALU	LE120ALU
Can the mirror be hung landscape?	-	Yes		
What is the thickness of the mirror glass?	mm	5		
Is the mirror IP44 rated?	-	Yes – Suitable for use in bathroom zone 2		
What size fuse should I use?	-	Seek the advice of an electrician		
What is the total power consumption?	W	58	66	88
Does the mirror have an energy rating?	-	Yes – It has an energy rating of: A		
What is the colour of the light and the Kelvin rating?	K	6000		
What is the Lumen of the LEDs?*	Lms	2040	2424	3192
What is the wattage of the lights?	W	16	18	24
Where is the Touch sensor located?	-	Front Bottom Right		
Where is the shaver socket located?	-	Lower Right Side		
Can the LED lighting be replaced?	-	No**		
Can the Touch sensor be replaced?	-	No		
What is the output of the demister pad?	W	13	19	37
What are the dimensions of the demister pad? (L x W)	mm	250 x 350	300 x 400	300 x 750
How do I turn on the demister pad?	-	The demister pad will turn on when the LEDs are turned on.		
Are illuminated mirrors supplied with mains cable?	-	All illuminated mirrors are supplied with a removeable 500mm mains cable. There is ample storage for excess cable in the back of the unit.		


Dimensions are subject to change; customers are advised to measure actual product before commencing installation.

Fixing point dimensions are for guidance only/the positions of wall fixing must be checked when product is received.


*The Lumen represents the output of the LED. This may vary depending on the diffuser material i.e., glass or acrylic.

**The LEDs are not replaceable to maintain the integrity of the product's resistance to moisture ingress

LE70ALU



LE80ALU



LE120ALU

