

thermo Sphere

Waterproofing Paste



A premium grade, rapid drying, highly flexible one part liquid rubber Waterproofing Paste.

- Advanced liquid rubber membrane.
- 100% waterproof and highly flexible.
- Easy to apply with no priming required.
- Rapid drying - tile over in 1 hour.
- Interior, exterior, domestic and commercial.
- Excellent adhesion.
- Solvent free.
- Ideal for showers, wetrooms, bathrooms, steam rooms, balconies and terraces.

Technical data

Code	HDMP-WP-01
Form	Ready to use liquid paste
Colour	Grey
Size	5KG
Durability	Up to 25 years when used as recommended
Elongation	>1000%
Warranty	10 years

Waterproofing Paste

Technical data

Specific gravity	1.4 - 1.5
pH	8.5 - 9.5
Flashpoint	None
Application temperature range	+6°C to +30°C (optimum +10°C to +20°C)
Application rates	Wall minimum 1mm. Floors minimum 1.5mm
Curing time	Approximately 1 hour (subject to site conditions)
Service temperature range	-20°C to 120°C
Shelf life	Up to 12 months when stored in unopened containers in cool dry conditions within the recommended temperature range. Avoid frost and extremes of temperature.
Clean up	Wash tools and equipment in water before it cures. Cured material is water resistant.

Surfaces and coverage

Surface type	Thickness (mm)	Coverage
Walls	1mm (minimum)	1.5kg/m ²
Floors	1.5 (minimum)	1kg/m ²
Joints	See wall or floor thickness	300g/Lm