

Technical Datasheet

Façade-U Cabinets

TAVISTOCK

Box Contents

Façade Cabinet | 2 smoked glass shelves | 2 Mirror Side Panels | Fixing Kit | Instructions booklet.
Recessed and surface mounted installation options.

FAQ

	Units	FCC050U	FCC060U	FCC080U	FCC100U
Recess dimensions (W x H x D)	mm	440 x 648 x 101	600 x 648 x 101	800 x 648 x 101	1000 x 648 x 101
Internal dimensions (W x H x D)	mm	410 x 555 x 98	570 x 555 x 98	770x 555 x 98	970 x 555 x 98
Shelf dimensions (W x H x D)	mm	404 x 5 x 95	564 x 5 x 95	764 x 5 x 95	964 x 8 x 95
Max shelf spacing	mm	250	250	250	250
Distance between door hinges	mm	370	370	370	370
Individual door dimensions (W x H x D)	mm	440 x 662 x 16	298x 662 x 16	398 x 662 x 16	498 x 662 x 16
Door opening angle	°	90	90	90	90
Depth with door fully open	mm	552	412	512	612
Hanging bracket centres	mm	390	550	750	950
What is the thickness of the mirror glass?	mm	3+3mm	3+3mm	3+3mm	3+3mm
What size fuse should I use?	-	Seek the advice of an electrician			
Where is the Touch Sensor located?	-	Lower right corner	Centre		
Can the LED lighting be replaced?	-	No			
How do I turn on the demister pad?	-	The demister pad will turn on when the LEDs are turned on.			
Are illuminated cabinets/mirrors supplied with mains cable?	-	All illuminated cabinets/mirrors are supplied with a removeable 500mm mains cable. There is ample storage for excess cable in the back of the unit.			

Technical Datasheet

Façade-U Cabinets

Electrical Specification

Product Code	Input Voltage	Lamp Type	Total Wattage (LED & Demist)	Demist (W)	Demist Size (mm)	LEDs (W)	LED (lm)	Energy Rating	CCT (K)	CRI	IP Rating	Electrical Class
FCC050U	220-240V 50Hz	12V DC LED Lamp	27.0	15.0	200x300	12.0	900	F	6000	85	IP44	Class I
FCC060U	220-240V 50Hz	12V DC LED Lamp	42.0	30.0	150x400	12.0	900	F	6000	85	IP44	Class I
FCC080U	220-240V 50Hz	12V DC LED Lamp	42.0	30.0	200x300	12.0	900	F	6000	85	IP44	Class I
FCC100U	220-240V 50Hz	12V DC LED Lamp	42.0	30.0	200x300	12.0	900	F	6000	85	IP44	Class I

Please note:

- Dimensions are subject to change. Customers are advised to measure actual product dimensions before commencing installation.
- Fixing point dimensions are for guidance only/the positions of wall fixing must be checked when product is received.
- The LED (lm) values represent the output of the LED. Actual product level Lumen output may vary depending on the diffuser material i.e., glass or acrylic.