Technical Datasheet

Oxygen Mirrors

TAVISTOCK

Box Contents
Oxygen Mirror | Fixing Kit | Instructions booklet

FAQ

	Units	XGM60C-XX	XGM50P-XX	XGM80C-XX					
Can the mirror be hung landscape?	170	Portrait Only							
What is the thickness of the mirror glass?	mm	5							
What size fuse should I use?	#3	Seek the advice of an electrician							
Where is the switch sensor located?	(=)	Front Centre							
Can the LED lighting be replaced?	-	No							
Can the switch sensor be replaced?		Yes							
How do I turn on the demister pad?	#	The demister pad will turn on when the LEDs are turned on.							
Are illuminated mirrors supplied with mains cable?	-	All illuminated cabinets/mirrors are supplied with a removeable 500mm mains cable.							
Why are the lights not switching on?		Please note: After the mirror is connected to power for the first time, it may take up to 5 minut for the sensor to calibrate and become fully responsive.							

Electrical Specification

Product Code	Input Voltage	Lamp Type	Total Wattage (LED & Demist)	Demist (W)	Demist Size (mm)	LEDs (W)	LED (lm)	Energy Rating	CCT (K)	CRI	IP Rating	Electrical Class
XGM60C-XX	220-240V 50Hz	24V DC LED Lamp	25.6	11	200x250	16.6	1950	F	3000-6500	80	IP44	Class II
XGM80C-XX	220-240V 50Hz	24V DC LED Lamp	46.3	23.1	300x350	23.2	2730	F	3000-6500	80	IP44	Class II
XGM50P-XX	220-240V 50Hz	24V DC LED Lamp	32.4	13.2	300x350	19.2	2262	F	3000-6501	80	IP44	Class II