



All dimensions shown are in millimetres

Construction: **100mm x 80mm extruded sections**

Connections: **1.2m long flying lead (2 core)**

Model	Height $\pm 2mm$	Width $\pm 2mm$	Finish	No. of Sections	Output Watts	Weight kg
ALE-050-036/F	575	377	painted	3	500	7.0
ALE-075-046/F	575	477	painted	4	750	9.0
ALE-100-056/F	575	577	painted	5	1000	11.0
ALE-125-076/F	575	777	painted	7	1250	15.0
ALE-150-086/F	575	877	painted	8	1500	17.0
ALE-200-116/F	575	1177	painted	11	2000	23.0

Issue 1.0

Tools & Material Required

Screwdriver
Electric drill
Masonry drill bit

Key	Component	Qty
A	Horizontal Levelling Piece	1
B	Bracket	2
C	Spirit Level	1
D	Wall Plug	4
E	Fixing Lug	2
F	Screw, 6mm dia x 50mm	4

Assembly Instructions

Attach horizontal levelling piece (A) to two brackets (B).

Accurately mark out bracket holes on wall using spirit level (C), to dimensions as shown on Technical Data Sheet.

Drill four holes to a minimum depth of 65mm & insert wall plugs (D).

Fix brackets (B) to wall with screws (F) then remove horizontal levelling piece (A) and spirit level (C).

Attach fixing lug (E) to rear of radiator.

Hang bottom of radiator onto bottom of bracket (B) then push top of radiator back until lug (E) locates in top of bracket (B). Tighten screw in lug (E) to secure radiator in place

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

