



## Abacus

PRODUCT	DIMENSIONS			PIPE CENTRES mm	FUEL OPTIONS E/H/D	PIPES OR SECTIONS	HEAT OUTPUT ΔT 50	
	Height mm	Length mm	Depth mm				BTU	Watts
ABACUS10-70RAL	950	460	45	50-550	E/H/D	10	3349	982
ABACUS10-70RAL-VARI	950	460	45	50-550	E/H/D	10	3349	982
ABACUS10-70SIL	950	460	45	50-550	E/H/D	10	3349	982
ABACUS10-70LUM	950	460	45	50-550	E/H/D	10	3349	982
ABACUS10-70GOLD	950	460	45	50-550	E/H/D	10	3349	982
ABACUS16-95RAL	1600	460	45	50-550	E/H/D	10	5159	1513
ABACUS16-95RAL-VARI	1600	460	45	50-550	E/H/D	10	5159	1513
ABACUS16-95SIL	1600	460	45	50-550	E/H/D	10	5159	1513
ABACUS16-95LUM	1600	460	45	50-550	E/H/D	10	5159	1513
ABACUS16-95GOLD	1600	460	45	50-550	E/H/D	10	5159	1513

SS Material   
 S Finish   
 10 Working Pressure   
 120°C Working Temperature   
 O C Open/Closed System   
 V Mounting Position   
 20 YEARS Warranty

Abacus is available in a multitude of finishes and can be fully customised to suit your preference.

### Abacus codes explained

**SRAL:** Globes produced in any one chosen RAL colour, on brushed matt stainless steel tubes

**SRAL-v:** Globes in a selection/multiples of any chosen RAL colour, on brushed matt stainless steel tubes

**SSIL:** Globes in a silver finish, on brushed matt stainless steel tubes

**SLUM:** Luminescent globes, on brushed matt stainless steel tubes

**SG:** Globes in a gold finish, on brushed matt stainless steel tubes