



## Arat E

PRODUCT	DIMENSIONS			PIPE CENTRES	FUEL OPTIONS	PIPES OR SECTIONS	HEAT OUTPUT	
	Height mm	Length mm	Depth mm				$\Delta T 50$	
							BTU	Watts
<b>ARARATE85050</b>	500	390	40	350	E/H/D	8	1441	422
<b>ARARATE10-5050</b>	500	490	40	450	E/H/D	10	1790	524
<b>ARARATE12-5050</b>	500	590	40	550	E/H/D	12	2138	626
<b>ARARATE14-5050</b>	500	690	40	650	E/H/D	14	2493	730
<b>ARARATE16-5050</b>	500	790	40	750	E/H/D	16	2835	830
<b>ARARATE20-5050</b>	500	990	40	950	E/H/D	20	3532	1034

PRODUCT	DIMENSIONS			PIPE CENTRES	FUEL OPTIONS	PIPES OR SECTIONS	HEAT OUTPUT	
	Height mm	Length mm	Depth mm				$\Delta T 50$	
							BTU	Watts
<b>ARARATE8-6060</b>	600	390	40	350	E/H/D	8	1730	506
<b>ARARATE10-6060</b>	600	490	40	450	E/H/D	10	2148	629
<b>ARARATE12-6060</b>	600	590	40	550	E/H/D	12	2566	751
<b>ARARATE14-6060</b>	600	690	40	650	E/H/D	14	2992	876
<b>ARARATE16-6060</b>	600	790	40	750	E/H/D	16	3402	996
<b>ARARATE20-6060</b>	600	990	40	950	E/H/D	20	4238	1241