

MILD STEEL RADIATORS



## K-FLAT KOMPACT HORIZONTAL

DIMENSION		TYPE 11 SINGLE CONVECTOR				TYPE 22 DOUBLE CONVECTOR			
HEIGHT (MM)	WIDTH (MM)	CODE	DEPTH (MM)	TAPPING CENTRES (MM)	OUTPUT (BTU) Δ T60	CODE	DEPTH (MM)	TAPPING CENTRES (MM)	OUTPUT (BTU) Δ T60
400	600	KS406F	56	600	1586	KD406F	105	600	3133
400	800	KS408F	56	800	2115	KD408F	105	800	4178
400	1000	KS410F	56	1000	2644	KD410F	105	1000	5222
400	1200	KS412F	56	1200	3173	KD412F	105	1200	6266
400	1400	KS414F	56	1400	3701	KD414F	105	1400	7311
400	1600	KS416F	56	1600	4230	KD416F	105	1600	8355
500	400	KS504F	56	400	1279	KD504F	105	400	2499
500	600	KS506F	56	600	1918	KD506F	105	600	3748
500	800	KS508F	56	800	2558	KD508F	105	800	4997
500	1000	KS510F	56	1000	3197	KD510F	105	1000	6247
500	1200	KS512F	56	1200	3837	KD512F	105	1200	7496
500	1400	KS514F	56	1400	4476	KD514F	105	1400	8746
500	1600	KS516F	56	1600	5116	KD516F	105	1600	9995
600	400	KS604F	56	400	1489	KD604F	105	400	2876
600	600	KS606F	56	600	2233	KD606F	105	600	4314
600	800	KS608F	56	800	2977	KD608F	105	800	5752
600	1000	KS610F	56	1000	3722	KD610F	105	1000	7190
600	1200	KS612F	56	1200	4466	KD612F	105	1200	8627
600	1400	KS614F	56	1400	5211	KD614F	105	1400	10065
600	1600	KS616F	56	1600	5955	KD616F	105	1600	11503
600	1800	KS618F	56	1800	6699	KD618F	105	1800	12941
600	2000	KS620F	56	2000	7444	KD620F	105	2000	14379

**10** Year Guarantee

**White**  
Gloss



Delivery within  
**2 Working Days**



MINIMUM INSTALLATION FROM THE FLOOR: 100MM

**TYPE 11**  
WALL TO TAPPING CENTRES  
40 OR 55MM

**TYPE 22**  
WALL TO TAPPING CENTRES:  
82.5 OR 97.5MM